

# USER MANUAL FOR



## *Boat Covers Now*

### **Cautions:**

1. Be sure your cover is dry.
2. Never pull the strap too hard while using it to tie the cover up.

### **Clean & Care:**

To clean your cover, please do not use soap. We suggest cleaning with cold or warm water and then lightly clean the boat cover with a sponge. It is not recommended to wash your cover in a washing machine, as it may cause premature wear of the cover. Before covering for long-term storage, please make sure your boat is dry. When the cover is not in use, please hang it to dry and fold it up.

### **Installation of Boat Cover:**

- 1 Find the sewn-in tag marked “Front” and drape the cover over your boat, positioning the sewn-in tag at the front of the boat. Hook the front of the cover over the nose of the boat.
- 2 Pull the cover toward the rear of the boat, making sure the cover is evenly distributed along all sides of the boat.
- 3 Locate loops on the boat cover. Take out the straps with plastic buckles (including male and female buckles) from the accessory polybag, route one side of the straps to the loops and through the trailer, then tie it with the other side of the strap. Tighten the straps on the trailer to keep the cover right above the boat.
- 4 After installing, inspect the cover and check that any possible abrasion points are adequately padded. Avoid any low points or valleys that could accumulate water.
- 5 It is recommended to buy a support rod by yourself.

### **After-Sale Services:**

If there is any question, please contact us through [sales@boatcoversnow.com](mailto:sales@boatcoversnow.com) and we will provide support within 24 hours.

